

The Most Powerful **HD-SDI** DVR

FKD-104S(4ch)
1080p@120fps, 1.5U



Features

- 1.5U, 4ch HD-SDI DVR
- 1080p@120fps, 1eSATA, Integrated POS
- 4ch Video Input, 1 Spot Output, 1 HDMI
- 1 VGA, & 1 BNC Output, 4ch Audio Input/1ch Output
- 4ch Alarm Input/1ch Output, VGA/BNC Sub Monitor Output
- SATA Drive Comparable, USB Mouse, Remote Control
- Dynamic IP Support, Two-way Network Audio, Archiving to USB
- 2 HDD Slots (or 1 HDD & 1 eSATA)
- iPhone & Android App (HDVIEWER)
- HDD is not included

Dimensions

Units: mm



Rear Panel



Model	FKD-104S
Operating System	Embedded Linux - Built in flash memory
Language	Multi-language Support
Time Sync	NTP, GMT, DST, Time Server 5ppm (12.5sec/month)
User	15 User (Admin, User1 ~ User14)
Video	
Input	4 BNC
Output	1 HDMI, 1 VGA, 1 BNC
Loop	N/A
Spot	1 BNC
Universal	Yes
Audio	
Input	16/8/4 RCA
Output	1 HDMI, 1 RCA
Recording Compression	G.711u
Video Recording	
Speed	Real time Recording (480fps / 240fps/ 120fps)
Resolution	1080p, 720p, 960H, D1, CIF
Quality	5 Levels
Bit Rate	512Kbps ~ 5Mbps/Ch, Adjustable
Network	
Interface	10/100/1G
Speed	Max 720p 8fps/ch
Compression	H.264/MJPEG
Resolution	Max.1280x720p
Alarm	
Post Alarm	5sec ~5min
Motion Grid	14x15(NTSC/PAL)
Alarm Action	E-mail, Ch Popup, Buzzer, Relay, PTZ Preset, Spot
Input / Output	4/1 - NC / NO/ EOL
Display	
HDMI	Full HD, XGA
VGA	Full HD, XGA
TV	SDTV(720x480/576)
General	
PTZ Keyboard	RS485-Terminal Block / Ethernet
ATM / POS	RS232C Terminal Block / Ethernet
Storage	2 HDD or 1HDD+eSATA
Operating System	Embedded Linux
Dimensions	340 x 59 x 300 mm
Net Weight (w/out HDD)	3Kg
Power Supply	12V/5A - Level 5
Consumption	40 Watts
Operating Temp	5~40°C
Humidity	10~80%