



MegaVue Series

**2MP | 1080P | TRUE D&N
ICR**

Features

- MegaVue 2MP, 1080P, HD-SDI
- True Day & Night ICR
- DWDR
- 3DNR, Sense-up, OSD
- Dual Voltage (24V AC / 12V DC)

Specifications

MODEL	SCG-A5C
IMAGE SENSOR	1/2.9" 2.1Megapixel Sony Exmor CMOS
EFFECTIVE PIXEL	1920 (H) × 1080 (V) = 2.07M
SCANNING SYSTEM	Progressive
VIDEO OUTPUT	HD_SDI, CVBS : 1.0Vp-p, 75Ω composite
S/N (Y Signal)	More than 52dB
Min. ILLUMINATION	0.02Lux(Sen-UP X32)
IRIS ADJUSTMENT	ALC/ESC
LENS	-
SHUTTER	OFF/AUTO(1/30~1/50,000)FLK / MANUAL(x2~x30)
OSD LANGUAGE	ENG/CHN/CHN[S]/JPN/KOR
BACKLIGHT COMPENSATION	OFF /HLC/BLC/WDR
DAY & NIGHT	COLOR/BW/EXTERN/AUTO
AUTO GAIN CONTROL	LEVEL(0~20)Adjustment
WHITE BALANCE	AUTO/AUTODEXT/PRESET/MANUAL
COMMUNICATION	RS485 (OPTION)
DEFECT	LIVE DPC/ DPC SET
PRIVACY MASKING	On / Off (Programmable 16 zones)
DNR	2DNR+3DNR(LEVEL Adjustment)
ACE	OFF/LOW/MIDDLE/HIGH
DEFOG	OFF/LOW/MIDDLE/HIGH
DIGITAL ZOOM	OFF/ON (x1 ~ x8.0)
SENS-UP	OFF/ X2~X32
MOTION	4 AREA
DIGITAL EFFECT	OFF / V-FLIP / MIRROR / ROTATE
DEFECT	LIVE DPC/ DPC SET
COMMUNICATION	RS 485 (OPTION)
IR LED	-
INPUT VOLTAGE	DC 12V(±10%) / AC 24V DUAL VOLTAGE
POWER CONSUMPTION	DC IR OFF : 200mA(±10%) / IR ON : 500mA(±10%) AC IR OFF : 190mA(±10%) / IR ON : 430mA(±10%)
OPERATING TEMP. / HUM.	-10°C ~ +50°C / MAX 90% RH
STORAGE TEMP. / HUM.	-20°C ~ +60°C / MAX 90% RH

Dimensions

