

Mini Indoor PTZ, 12X Samsung Zoom, 550TVL, ICR, I/O, HLC, DIS, SNR, 24VAC

EPTI-M12T



Features

- No Accumulative Error with Preset Function
- Shortest Path by Vector Drive Technology
- High Accuracy with Micro-Stepping Control Technology
- Smooth Motion at High Zoom Magnification Mode
- Lightening Speed (MAX. 360°/sec) & Smooth Manual Speed (MIN. 0.05°/sec)
- Lowest Noise & Lowest Vibration
- Endless 360° Pan Rotation
- X144 Zoom Control (Optical X12, Digital X12)
- Day & Night (IR Cut Filter)
- SNR (Super Noise Reduction)
- Independent Preset Parameter Setup (AE, WB and etc.)
- 127 Preset Positions with Alphanumeric Labels
- 4 Pattern, 8 Swing and 8 Group Functions
- 4 Privacy Masks (Spherical Coordinates)
- Auto Flip, Auto Parking, Power-up Action
- Frame Freeze Function
- On-Screen Display On/Off
- Small Size

Specifications		
Camera	Image Device	Sony 1/4" Interline Transfer CCD
	H. Resolution	560 TV Lines(Color), 600 TV Lines(B/W)
	S/N Ratio	50dB (AGC Off)
	Zoom	X12 Optical Zoom and X12 Digital Zoom
	Focal Length	F1.6(Wide)/F2.0(Tele), f=3.6 ~ 44.3mm
	MIN. Illuminance	1.2 Lux (Color)_Sens off / 0.0004 Lux (B/W)_Sens x256 @ 50 IRE / F1.6
	Day & Night	Auto / Day / Night (IR Cut Filter)
	Focus	Auto / Manual / Semi-Auto
	Iris	Auto / Manual
	Shutter Speed	x128 ~ 1/120000 sec
	AGC	Normal / High / Off
	White Balance	Auto / Manual (Red & Blue Gain Adjustable)
	BLC	Low / Middle / High / Off
	Flickerless	Selectable
	SSNR	Low / Middle / High / Off
	Privacy Mark	4 Masks with Spherical Coordinates
	Other Functions	Frame Freeze Function
Pan/Tilt	Range	Pan : 360° (Endless) / Tilt : 90° Preset : 360° / sec
	Pan/Tilt Speed	Manual : 0.05° ~ 360° / sec (Zoom Proportional)
		Swing : 1° ~ 180° / sec
	Preset	127 Presets with Labels / Independent Preset Parameter Setup
	Pattern	4 Patterns (Approx. 5 Minutes for Each Pattern)
	Swing	8 Swings
	Group	8 Groups (MAX. 20 Entries for Each Group)
Other Functions	Auto Flip, Auto Parking, Power-up Action & etc.	
General	Communication	RS-485
	Protocol	Pelco-D, Pelco-P Selectable
	OSD	English On / Off
	Dimension	Dome : ø 107.5 mm / ø 4.2"
		Housing : 132(ø) x 129.5(H) mm / 5.2" (ø) x 5.1" (H)
	Weight	Approx. 0.8 Kg / 1.7 lbs
	Material	Dome : Poly Carbonate / Housing : ABS
	Environment	Indoor
	Operating Temp.	0° C ~ 40° C / 32° F ~ 104° F
Power	DC 12V / 0.8A	
Sensor In/Out	Not Available	

Specification & Design are subject to change without prior notice.