



Features

- 5MP Turret Camera
- 1/2.8" SONY Starvis Back-illuminated CMOS sensor
- 2.7-13.5mm Motorize Lens
- IR Distance: 120ft
- WDR, 3DNR, Defog, Smart-IR
- TVI/AHD: 5M@20fps/12.5fps, 4M/2M@30fps;
CVI: 4M/2M@30fps
- IP67

Specifications

Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Image Resolution	5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	Auto / Manual
Scanning System	Progressive Scan
Lens Focus Length	2.7-13.5mm
Lens Focus Control	Auto
Lens Type	Motorized
Starlight	Yes
Day/Night	Yes
OSD Menu	Yes
WDR	Yes
UTC	Yes
Noise Reduction	3DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO
Housing	Metal, IP67
Bracket	No
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 750mA
Dimension (WxDxH)	φ 119 x 98(H) mm
Weight	800g